

Giv-Bat 2.6





Remote Firmware

Control and monitor your Smart System on the move via our GivEnergy Monitoring App and Portal.



IP65 Rating

Our IP65 rated enclosure gives protection against water and dust. Ideal for lofts and outdoor installation.



10 Year Warranty

Supplied with a full manufacturers warranty, our dedicated UK support team are on hand to help you should any issues arise.



Retrofit Compatible

and start enjoying the benefits of our

GivEnergy Smart System.

The 2.6kWh battery pack sits alongside our AC Coupled or Hybrid Inverter so that you can store energy from the grid or excess generation.

Utilising lithium iron phosphate, our batteries are extremely safe and can be installed in a wide range of locations. Due to its light weight, it is ideal for installation in lofts and hard to access areas and can be banked together to increase capacity.

Dimensions (HxDxW) **369 x 220 x 480 (mm)**

Weight 32 Kg

Depth of Discharge

90 %

Capacity

2.6 kWh / 51 Ah



MODEL	2.6	5.2	8.2
Specifications			
Capacity	2.6 kWh / 51 Ah	5.2 kWh / 102 Ah	8.2 kWh / 160 Ah
Voltage		51.2V	
Current	30A Charge / Discharge	60A	85A
Technology		LiFePO ₄ Cell	
IP Grade		IP65	
BMS	Robust Multi Point Monitoring BMS Pre Installed		
Life Cycling (90% DOD, 25°C	10 Years		
Operating Temperature	-10°C - 55°C		
Storage Temperature		-30°C - 60°C	
Warranty BTT	26MWh / 10 Years	52MWh / 10 Years	Unlimited Cycles / 10 Years
Standard		UN 38.3, IEC61000	
Weight	32 Kg	54 Kg	94 Kg
Electrical Parameters	2.6	5.2	8.2
Operating Voltage Range		43.2V - 58.5V	
Maximum Charging Voltage		59V	
Max Charging / Discharging Current	30A / 30A	60A / 60A	85A / 85A
Network Interface		RS485	
Communication Protocols		Modbus	
Advantages	Stackable, BMS Upgradeable, IP65		
Depth of Discharge	90%	90%	100%

